Product datasheet

uvex 2 construction 6510 1-3

Safety boot DIN EN ISO 20345:2022+A1:2024 S3 FO LG SC SR
Sizes: 35 - 52 | Width: 10, 11, 12







AREA OF APPLICATION

Medium applications usually alternate between indoor and outdoor areas, meaning that the demands on the robustness of the outsole of a safety shoe are much higher.

OUTSOLE

Dual-density polyurethane sole



- PU outsole
- shock-absorbing PU midsole
- antistatic
- short-term heat-resistant up to 120°C
- excellent slip resistance (**SR**)
- oil- and fuel resistant (**FO**)
- free of silicones, plasticisers and other substances that interfere with wetting agents

FEATURES	
Upper material	• forefoot area: water-repellent uvex waterstop leather • heel area: hydrophobic leather • collar: hydrophobic microvelour • water-repellent (**WPA**)
Lining material	• textile distance mesh lining for comfortable foot climate (**clima** zone)
Fastening	• laces
Heel basket	• foamed heel basket out of PU for additional stability in the shoe
Reflecting elements	• for increased visibility even in dark working environments
Comfort	• soft padding on collar • sizes 35-40 have been produced using a women's last • dust tongue
Innersole	• removable comfortable innersole
PROTECTIVE FEATURES	
Toe cap	• metal-free protective toe cap
Penetration resistance	• steel penetration resistance
Scuffcap	• out of PU for additional protection of the upper material (**SC**)
Ladder grip	• support on ladders due to transversely inserted profile (**LG**)
CERTIFICATES	
uvex medicare+	• certified for orthopaedic innersoles and shoe adjustments according to the description in **DGUV 112-191**
PRODUCT INFORMATION	
Product Information	• free from harmful substances in accordance with the uvex restricted substances list • detailed information on material composition and recycled content can be found in the uvex catalogue
ACCESSORIES/ SPARE PARTS	
Replacement innersole	• 9534 7-0
Laces	• black 9599922